

## Office Off-Line Series

### Reliable Power Protection for Home and Office Computer

This series are specifically designed for personal computer and workstation applications. It offers dependable power protection in a light weighted, graceful and sleek design, fits nicely into today's modern office design.

This series can operate under a wide range of input utility power while maintain steady output voltage. This is especially critical for equipments that require consistent backup power or working under high utility fluctuation. As the increasing of computer peripherals in a computer system, additional surge protected outlets are provided to protect your printer, scanner or other peripheral devices from surges, spikes, and electromagnetic interference.

Besides providing power protection and EMI/RFI to output load, this series also provides surge and lightning protection for data/fax Modem line (RJ11) thus further enhancing the protection capabilities. With the outstanding cost-performance design, it is the best choice for home and office application all over the world.



#### Flat Pack Style UPS

- High Frequency Design.
- Resettable circuit Breaker.
- LEDs Display function
- Widely spaced outlets.
- Compact design fit on/under your desk or mounts on the wall.
- Surge protection for Modem / Fax / 10 Base T modular combinations.
- Three battery backup with surge protected outlets and three surge protected outlets.
- Battery Hot Swappable, Easy TO Access and Replaceable With Wireless Connection.

#### Specification

Model	Office CE 300	Office NT 400/600	Office Lighthouse 350/500
Topology		Line Interactive	
Capacity	300VA/150W	400VA/200W / 600VA/300W	350VA/175W / 500VA/250W
<b>Input</b>			
Nominal Voltage	120Vac	120Vac	230Vac
Frequency Range	50/60Hz+/-5Hz(Auto sensing)		
Voltage Range	102~138Vac	102~138Vac	187~253Vac
<b>Output</b>			
Nominal Voltage	120Vac	120Vac	230Vac
Frequency Regulation	50/60 ±0.5Hz		
Waveform	Simulated Sine Wave		
Transfer Time	6~10 ms typical, 10ms max		
No. of Outlets	3 pcs NEMA 5-15R Battery backup and surge protection 3 pcs NEMA 5-15R surge protection outlets	2 pcs NEMA 5-15R Battery backup and surge protection 2 pcs NEMA 5-15R surge protection	
Noise filter	Full time EMI/RMI filtering, 100KHz to 10MHz		
Protection	Overload, Short-circuit, Discharge, and overcharge protection		
<b>Battery</b>			
Battery Type	Sealed ,maintenance free, lead-acid battery		
Battery Capacity	12V/2.3Ah*1	12V/4.5Ah*1 @ 400VA 12V/5.0Ah*1 @ 600VA	12V/4.5Ah*1 @ 350VA 12V/5.0Ah*1 @ 500VA
Typical back up time	8 ~ 20 min		
Recharge Time	8 hours typical, 12 hours max		
<b>Surge Protection</b>			
TEL/FAX Surge Suppression	RJ11/45 (1 in / 1 out)		
Surge energy rating	380 joules	320 joules	220 joules
Surge current capability	6500 A		
Surge response time	0 ns normal mode, <5 ns common mode		
Surge voltage let through	0.7 subject to IEEE, 686 Cat. At 6KV test		
<b>Indicators</b>			
Display	LED Indicator		
Audible Alarms	Overload, On battery, Low battery, and self-test		
<b>Communication</b>			
Interface	USB(Optional)		
<b>Physical</b>			
Humidity (operating)	0 to 95% non condensing		
Temperature (operating)	0 ~ 40 °C, 0~95% RH, non condensing		
Dimensions (WxDxH)mm	114x67x279	122x84x305	130x85x335
Net Weight	1.8kg	3.0kg (400VA) / 3.3Kg (600VA)	2.7kg (350VA) / 2.8Kg (500VA)

Technical Specifications subject to change without notification.